

Hydrotech®

Flow Switch (Low Flow Rate – SPDT)

Description:

For use on liquid lines using water, ethylene glycol solutions, or other liquids not corrosive to the brass or phosphor bronze parts. The SPDT contact switch is activated by a low flow rate; however, it has a large flow capacity with a minimum pressure drop.

Applications:

- Water purification and treatment systems
- Booster pumps
- Fast shutdown on high input boilers to guard against circulation failure
- Cooling systems for electronic tubes, bearings, and compressors



F61KD-4

Item #	Description	Inlet and Outlet Size Female NPT	Enclosure NEMA Type	Adjustment Range - GPM (L/Min)		Maximum Liquid Temp	Minimum Liquid Temp	Maximum Liquid Pressure
				R to Y Closes Flow Increase	R to Y Opens Flow Decrease			
85251	F61KD-4C Flow Switch (Low Flow Rate - SPDT)	3/4" x 3/4" (19mm x 19mm)	1	Min 0.6 (2.27) Max 1.1 (4.17)	Min 0.3 (1.14) Max 0.9 (3.4)	250°F (121°C)	32°F (0°C)	150 psig (1034 kPa)

Your Local Water Treatment Professional

TOLL-FREE: 1-877-288-9888
www.hydrotechwater.com