

METAL STORAGE TANKS FOR REVERSE OSMOSIS APPLICATIONS

Water goes through a reverse osmosis membrane very slowly and people don't have the patience to wait a long time to get a glass of water. For this reason the residential RO units need a water storage tank to store the purified water. The RO tanks can deliver stable and constant water flow when the faucet is opened.

To avoid bad odors from the diaphragm, all of the tank diaphragms are post-cured before assembly, to eliminate the possibility of odors from the tank.

Tanks are NSF approved under standard 58, and CE approved under the PED (pressure equipment directive).



- ➔ Maximum Working Pressure: 100PSI
- ➔ All Tanks are Pre-charged at 7 PSI
- ➔ Fittings sold separately
- ➔ NSF 58 certified



| Item # | Description | Port | Capacity gal (liters) | Diameter inch (mm) | Height inch (mm) | Color | Shipping Weight lbs (kg) |
|--------|-------------|----------|-----------------------|--------------------|------------------|-------|--------------------------|
| 92371 | PRO-3.2 | 1/4" NPT | 3.2 (12) | 8.98 (228) | 13.8 (345) | White | 9.9 (4.5) |
| 92372 | PRO-11 | 3/4" NPT | 11 (41.6) | 14.97 (380) | 21.2(530) | Blue | 28 (12.7) |
| 92373 | PRO-20 | 3/4" NPT | 20 (71.7) | 14.97 (380) | 28.8 (720) | Blue | 39 (17.17) |

| Shut-off Valve for 1/4" NPT Tank Item # | Description |
|---|---|
| PPSV500822W | Shut Off Valve, 1/4" QC X 1/4" NPTF |
| PPSV501222W | Shut Off Valve, 3/8" QC X 1/4" NPTF |
| 80704 | Shut Off Valve, 3/8" Comp Nut X 1/4" NPTF |
| Shut-off Valve for 3/4" NPT Tank Item # | Description |
| 92295 | Kit, 3/8" Comp Nut Shut-off valve X 3/4" NPTF |